

···
Quick Clamping System

RPG 1.0 Cordless

Tube Squaring Machines

Burr-free and square preparation of thinwalled stainless steel tubes up to 1 inch.

The cost-effective tube end preparation for welds conforming to industry standards.

Advantages:

- High-quality machining results
- Burr-free and square tube ends
- High-Performance coated tool bit with two cutting edges
- Quick clamping system for tubes, tools and clamping shells
- No additional tools required for operation
- Space saving, lightweight and portable machine
- Built-in electronic speed regulation
- Micrometer feed for optimum results
- Feed unit twistable in cramped working areas

Your benefits:

- Low initial costs
- Increased productivity
- Reduced manufacturing costs
- Mobile and secure operation, easy handling
- Clean-room suitable



···∻ Portable Machine

precision. power. simplicity. High-Performance coated tool bit with two cutting edges (Code 790 038 314)

One-piece clamping shells for deformation-free clamping of thin-walled tubes Micrometer feed for optimum results

Feed unit twistable in cramped working areas

Tube Squaring Machines RPG 1.0 Cordless

Technical data	RPG 1.0 Cordless	RPG 1.0 Cordless right-angled drive
Dimensions	235 x 380 x 75 mm (9.25 x 15 x 3 inch)	145 x 380 x 75 mm (5.7 x 15 x 3 inch)
Total weight (with accumulator; without clamping shells)	2.1 kg / 4.63 lbs	2.2 kg / 4.85 lbs
Voltage of rechargeable accumulator	12 V	12 V
Power supply of battery charger	110 - 120 V, 50/60 Hz (Code 790 036 002)	110 - 120 V, 50/60 Hz (Code 790 036 012)
Speed (max. idling speed)	0 - 400 rpm	0 - 350 rpm
Noise level at the workplace	Idle running: approx. 70 dB (A) With load: approx. 85 dB (A)	Idle running: approx. 70 dB (A) With load: approx. 85 dB (A)
Vibration level according to EN 50144	< 2.5 m/s ²	< 2.5 m/s ²

Tube OD min max. 3.18 - 25.40 mm (0.125 - 1.000 inch) 3.18 - 25.40 mm (0.125 - 1.000 inch) Wall thickness max. 2 mm (0.079 inch) 2 mm (0.079 inch) Tube materials High allow steels, upplloyed and low allow steels, and aluminum. Others on request	Working range	RPG 1.0 Cordless	RPG 1.0 Cordless right-angled drive
	Tube OD min max.	3.18 - 25.40 mm (0.125 - 1.000 inch)	3.18 - 25.40 mm (0.125 - 1.000 inch)
Tube materials	Wall thickness max.	2 mm (0.079 inch)	2 mm (0.079 inch)
	Tube materials	High-alloy steels, unalloyed and low-alloy steels and aluminum. Others on request.	

The technical data are not binding. They are not warranted and characteristics are subject to change. Please consult our General Conditions of Supply.



© Orbitalum Tools GmbH (10.2007) / An ITW Company c/o Jetline Engineering, 15 Goodyear Street, Irvine, CA 92618, USA Phone: (949) 951-1515 Ext 133, Fax: (949) 544-7988 www.orbitalum.com, tools@orbitalum.com

ehemals / formerly known as Georg Fischer Rohrverbindungstechnik

+GF+